

#5
211
367.39878X00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

11040 U.S. PTO
09/033607
04/13/01

Applicant(s): DAM NIELSEN, et al
Serial No.: Not assigned
Filed: April 13, 2001
Title: A RADIO TERMINAL
Group: Not assigned

LETTER CLAIMING RIGHT OF PRIORITY

Honorable Commissioner of
Patents and Trademarks
Washington, D.C. 20231

April 13, 2001


Sir:

Under the provisions of 35 USC 119 and 37 CFR 1.55, the applicant(s) hereby claim(s) the right of priority based on United Kingdom Patent Application No.(s) 0009081.1 filed April 13, 2000.

A certified copy of said United Kingdom Application is attached.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Donald E. Stout
Registration No. 26,422

DES/amr
Attachment
(703) 312-6600

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


Dated

4 December 2000

THIS PAGE BLANK (USPTO)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

17APR00 E529403-1 D027410
P01/7700 0.00-0009081 Report
Gwent NP9 1RH

1. Your reference

2. Patent application number

(The Patent Office will fill in this part)

0009081.1

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NOKIA MOBILE PHONES LIMITED
KEILALAHDENTIE 4
02150 ESPOO
FINLAND

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

FINLAND

5911995004

4. Title of the invention

A RADIO TERMINAL

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

NOKIA IPR DEPARTMENT
NOKIA HOUSE
SUMMIT AVENUE
FARNBOROUGH
HAMPSHIRE
GU14ONG UK

Patents ADP number (if you know it) 7577638001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 10

Claim(s) 3

Abstract 1

Drawing(s) 14

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents

(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

JULIET HIBBERT

Date

13.4.00

12. Name and daytime telephone number of person to contact in the United Kingdom

Miss J Hibbert 01252 865101

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

A radio terminal

5 The present invention relates to a terminal and a method thereto for displaying information on a small display.

10 Some handheld devices, such as personal digital assistants (PDA), cellular phones, pagers as well as desk-top telephones, are capable of receiving and displaying different kind of information. This information is typically elements comprising a text based on alpha-numerical signs, but the elements can also comprise graphics. However, these types of devices uses a display of rather small size, which some users may experience as difficult to monitor. The difficulty lays often in how the information is presented on the display, which might differ depending on the information provider and/or the device itself.

15

One way of displaying the information would be to wrap a text and feed it vertically down the display, which might be preferable if the text is longer than the width of the display. If the text is longer than what can be continued in the number of lines displayable in the display the text is being clipped vertically, 20 the remaining text can be accessed by scrolling the text downwards. The scrolling could either be done manually, e.g. by pressing on a pre-defined key which activates the scrolling function, or automatically.

25 Another way of displaying information could be to display a text which is continuos, i.e. a text which shown on a single line. If the text is longer than the width of the display, the text can be scrolled across the display either manually, e.g. by pressing on a pre-defined key which activates the scrolling function, or automatically.

Also, these two ways of displaying, can be combined dynamically by the provider and/or the manufacturer. Thus, if some parts is considered as easier to monitor when displayed in one way, and vice versa, then the provider and/or the manufacturer can display the information in the preferred way. For example, the elements can be links displayed in a list, which can be scrolled down vertically. In order to do this quickly, it might be preferable to display the list as continuous text. However, if the elements are initially showing the same content on the display, and the remaining parts are not visible, then it might be preferred to wrap the text.

10

Here is an example of three elements to be displayed:

<http://wap.nokia.com/club.wml>

<http://wap.nokia.com/stock.wml>

15 <http://wap.nokia.com/net.wml>

Here is an example of how these three elements can be displayed as continuous text, which initially showing the same content on the display:

20 <http://wap.nokia.com/...>

<http://wap.nokia.com/...>

<http://wap.nokia.com/...>

Here is another example of how these three elements can be displayed as wrapped text:

25

<http://wap.nokia.com/>

club.wml

<http://wap.nokia.com/>

30 stock.wml

[http://wap.nokia.com/](http://wap.nokia.com/net.wml)
net.wml

Both of these two alternatives can be useful depending on what the user would like to do. However, there are very few possibilities for the user to affect the elements. Therefore, there is a need to improve and facilitate the possibilities to display the information on a display.

According to one aspect of the present invention there is provided a method for displaying information on a display, where the information is provided with elements. An element is either having a continuous length presenting a length which is equal to or greater than the size of said display, or a wrapped length presenting a length which is less than the size of said display. The display is further provided with a user interface having a menu structure of items. The user interface is provided with a selectable continuous length item and/or a wrapped length item. The information is displayed according to the selection made in the menu structure of the user interface, in order to allow the user to toggle between continuous length and wrapped length.

According to another aspect of the present invention there is provided a terminal for displaying information on a display. The information comprising elements, wherein an element is either provided with a continuous length presenting a length which is equal to or greater than the size of the display, or a wrapped length presenting a length which is less than the size of the display. The terminal comprising a display for displaying the information, and a user interface provided with a menu structure comprising a selectable continuous length item and/or a wrapped length item. The items are arranged to display the information according to a selection made in the menu structure, in order to allow the user to toggle between continuous length and wrapped length.

According to a third aspect of the present invention there is provided a terminal for displaying information on a display. The information comprising elements, wherein an element is either provided with a continuous length
5 presenting a length which is equal to or greater than the size of the display, or a wrapped length presenting a length which is less than the size of the display. The terminal comprising a display for displaying the information, means for setting a first type of elements to be displayed as a continuous
10 length item and a second type of element to be displayed as a wrapped length item. Also, the terminal comprising means for identifying the first type of element when acting in a text to be displayed, and means for displaying the first and second type of elements according to their setting.

For a better understanding of the present invention and to understand how
15 the same may be brought into effect reference will now be made by way of example only to the accompanying drawings in which:

Figures 1 and 2 schematically illustrate a radio handset ;

20 Figure 3 is a flowchart illustrating one aspect of the present invention; and

Figure 4 illustrates a user interface according to an embodiment of the present invention.

25 Fig. 1 shows a preferred embodiment of a terminal, hereafter also referred as a phone, according to a preferred embodiment of the invention. The phone, which is generally designated by 1, comprises a user interface having a keypad 2, a display 3, an on/off button 4, a speaker 5, a microphone 6a and a transducer 6b. The phone 1 according to the preferred embodiment is
30 adapted for communication via a wireless telecommunication network, e.g. a

cellular network. However, the phone could also have been designed for a cordless network. The keypad 2 has a first group 7 of keys as alphanumeric keys, by means of which the user can enter a telephone number, write a text message (SMS), write a name (associated with the phone number), etc. Each of the twelve alphanumeric keys 7 is provided with a figure "0-9" or a sign "#" or "*", respectively. In alpha mode each key is associated with a number of letters and special signs used in text editing.

The keypad 2 additionally comprises two soft keys 8, two call handling keys 9, and a navigation key 10.

The two soft keys 8 have a functionality corresponding to what is known from the phones Nokia 2110™, Nokia 8110™ and Nokia 3810™. The functionality of the soft key depends on the state of the phone and the navigation in the menu by using a navigation key. The present functionality of the soft keys 8 is shown in separate fields in the display 3 just above the keys 8.

The two call handling keys 9 according to the preferred embodiment are used for establishing a call or a conference call, terminating a call or rejecting an incoming call.

The navigation key 10 is an up/down key and is placed centrally on the front surface of the phone between the display 3 and the group of alphanumeric keys 7. Hereby the user will be able to control this key by simply pressing the up/down key using his/her thumb. Since many experienced phone users are used to one-hand control, it is a very good solution to place an input key, requiring precise motor movements. Thus, the user may place the phone in the hand between the finger tips and the palm of the hand. Hereby, the thumb is free for inputting information.

The transducer 6b could be a buzzer, and is arranged to generate a sound of a ring tone, upon reception of a signal from another phone, e.g. an incoming call or reception of an SMS (short messaging service) message.

5 Fig. 2 schematically shows the most essential parts of a preferred embodiment of the phone. These parts being essential to understand the invention. The preferred embodiment of the phone of the invention is adapted for use in connection with a GSM network, but, of course, the invention may also be applied in connection with other phone networks, such as other kinds
10 of cellular networks and various forms of cordless phone systems or in dual band phones accessing sets of these systems/networks. The microphone 6a records the user's speech, and the analogue signals formed thereby are A/D converted in an A/D converter (not shown) before the speech is encoded in an audio part 14. The encoded speech signal is transferred to controller
15 means 18, which may support software in the phone. The controller means 18 also forms the interface to the peripheral units of the apparatus, including a RAM memory 17a and a Flash ROM memory 17b, a SIM card 16, the display 3 and the keypad 2 (as well as data, power supply, etc.). The controller means 18 communicates with the transmitter/receiver circuit 19. The audio
20 part 14 speech-decodes the signal, which is transferred from the controller 18 to the earpiece 5 via a D/A converter (not shown).

Also, the audio part 14 is also able to give an output of an ring tone to the buzzer 6b. The ring tone can be stored in either of the memories 17a,b, and is
25 recalled when the receiver 19 receives an incoming signal, by means of the controller 18. Thus, the ring tone is recalled from the memory, forwarded to the audio part 14, and the ring tone is generated as an output from the buzzer 6b.

The controller means 18 is connected to the user interface. Thus, it is the controller means 18 which monitors the activity in the phone and controls the display 3 in response thereto.

- 5 Therefore, it is the controller means 18 which detects the occurrence of a state change event and changes the state of the phone and thus the display text. A state change event may be caused by the user when he activates the keypad including the navigation key 10, and these type of events are called entry events or user events. However, the network communicating with the
- 10 phone may also cause a state change event. This type of event and other events beyond the user's control are called non user events. Non user events comprise status change during call set-up, change in battery voltage, change in antenna conditions, message on reception of SMS, etc.
- 15 Figure 3 shows a flowchart over a method for displaying information on a display, in accordance with the present invention. The information is provided with elements. An element is either having a continuous length presenting a length which is equal to or greater than the size of the display, or a wrapped length presenting a length which is less than the size of said display. The
- 20 display is further provided with a user interface having a menu structure of items.

In order to allow the user to toggle between continuous length and wrapped length, the user is first able to select a display menu "SELECT DISPLAY

25 MENU". In this menu, the user interface is provided with a selectable continuous length item and/or a wrapped length item "SELECT AN ITEM". If the present text is set as wrapped text, and the user would like to change it into continuous text, the user would perhaps like to choose the continuous length item, "CONT. OR WRAPPED?". Thereafter, the information is finally

displayed according to the selection made in the menu structure of the user interface, which in this case was "DISPLAY TEXT CONTINUOSLY".

As an alternative solution, in accordance with the present invention, the selection could be done automatically. This is done by providing the terminal with means for setting a first type of elements to be displayed as a continuous length item and a second type of element to be displayed as a wrapped length item. The terminal also comprising means for identifying the first type of element when acting in a text to be displayed, and means for displaying the first and second type of elements according to their setting.

With reference to Fig. 4a and 4b, an example is shown on how the display in a user interface can act by interaction of the user according to the present invention. The user interface may comprise the same elements as shown in Fig.1, i.e. a keypad 2, a display 3, an on/off button 4, a speaker 5 and a microphone 6. Also, it is the control means 18 in Fig. 2 which controls the user interface. Starting from Fig. 4a, there is a layout 30 presented on a display in a phone, as shown in Fig.1 and 2, which indicates signal strength 35 from the wireless telecommunication network "D1 Telekom" 40, the battery power 45 and a clock showing the time 50 in hours and minutes. Preferably, the display in the phone is an LCD (Liquid Crystal Display) display. The display, can be controlled by the control means 18 as shown in Fig. 2. The layout 30 presents an example of the phone in idle mode, i.e. when the phone is activated and awaiting an action, e.g. an incoming or outgoing call. In the bottom of the display there are two items which are denoted as "Menu" 55 and "Names" 60. If the user selects "Names" 60 he/she can e.g. access a built in phone book. If the user selects "Menu" 55, he/she can select among several different menus. The actual selection of features in the bottom of the display, like "Menu" and "Names", can be selected by means of the soft keys disclosed with reference to Fig. 1.

One of the menus can be the next layout 65 called "Browser" 70. If the user chooses to use this menu, he/she can access different telecom related information services, e.g. Internet. One way of accessing this kind of information is to use the Wireless Application Protocol, WAP. The Wireless Application Protocol (WAP) is a result of continuous work to define an industry wide standard for developing applications over wireless communication networks. WAP is disclosed in the Wireless Application Protocol Architecture Specification; Version 30-Apr-1998; by Wireless Application Protocol Architecture Working Group.

If the user chooses to select "Home" 71, this may lead to the next layout 75, which graphically indicates, "Connecting to Service" 80. This shows an example of how the phone is trying to establish a connection to e.g. Internet, by sending an access request to a server. If a connection is established, some kind of welcome text for a home page might be displayed, "Welcome to D1 Web." 90. If the user selects "Options" 100 a list of selections can be displayed as shown in the following layout 110. For example, the different choices could be different links or just plain text, wherein a link is indicated by the underline "This is a ..." 120, 125 and a plain text have no underlining "This is a ..." 130. The dots "..." indicates that not all the text is visible, and is an example of continuous text. The text is typically alpha-numerical.

In this example the user selects to continue with pressing on the softkey as is indicated as Options 135, which brings us to the next layout 140. This layout shows a menu structure of items; "Home" 145, "Bookmarks" 150, "Select" 155 and "Display options" 160. The text which is inverted in "Display options" 160 is selected by 165, which brings us to Fig. 4b and the layout for Display options 170. In this layout the user has the following choices: Font 175, Size

180, Wrapped text 185 and Continuous text 190. In accordance with the present invention, the user is allowed to toggle between the continuous length (as shown in layout 110) and wrapped length, by providing a selectable item of either "Wrapped text" 185 or "Continuous text" 190. Other items are also shown in this layout, like Font 175 and Size 180, which gives the user further choices to adopt the text in a preferred manner. Since the information displayed in layout 110 is continuous and not all information is visible, the user chooses in this example to select Wrapped text 185.

- 10 By selecting Wrapped text the text in layout 110 is changed to be displayed like the text in layout 200. Now, the user is able to read the whole text of the first text "This is a first link" 205 and a part of the second text "This is a" 210. When the user scrolls down the text in the display, by using navigation key 10 (Fig. 1), the remaining text from layout 110 is now visible from layout 215 and
15 220.

- Although the invention has been described with respect to a particularly preferred embodiment, it should be appreciated that the invention as defined by the claims extends beyond the particular features of the embodiment
20 described to encompass modifications and variations to the embodiment not necessarily described.

CLAIMS:

1. A method for displaying information on a display, said information having
5 elements, wherein an element having either a continuous length presenting
a length which is equal to or greater than the size of said display, or a
wrapped length presenting a length which is less than the size of said
display, and said display is further provided with a user interface having a
menu structure of items, said method comprising the following steps:
10 - providing in said menu structure a selectable continuous length item and/or
a wrapped length item,
- selecting said continuous length item or said wrapped length item in the
menu structure of the user interface, and
- displaying said information according to the selection made in the menu
15 structure of the user interface, in order to allow the user to toggle between
continuous length and wrapped length.
2. A method according to claim 1, wherein said information is displayed as
alpha-numerical signs.
20
3. A method according to claim 1 or 2, wherein said element, having a
continuous length, is scrolled over said display.
4. A method according to claim 1 or 2, wherein the element, having a
25 wrapped length, is adopted to fit the size of the display, by splitting the
element into several parts each part fit in the size of the display and
feeding said parts in a vertical direction over said display, each time the
length of the element is greater than the width of the display.

5. A terminal for displaying information on a display, said information comprising elements, wherein an element is either provided with a continuous length presenting a length which is equal to or greater than the size of said display, or a wrapped length presenting a length which is less than the size of said display, said terminal comprising
- 5
- a display for displaying said information; and
 - a user interface provided with a menu structure comprising a selectable continuous length item and/or a wrapped length item, said items are arranged to display said information according to a selection made in the
- 10 menu structure, in order to allow the user to toggle between continuous length and wrapped length.
6. A terminal according to claim 5, wherein said information is alpha-numerical.
- 15
7. A terminal according to claim 5 or 6, wherein said element, having a continuous length, is arranged to be scrolled over said display.
8. A terminal according to claim 5 or 6, wherein the element, having a wrapped length, is arranged to split the element into several parts each
- 20 part fit in the size of the display and to feed said parts in a vertical direction over said display, each time the length of the element is greater than the width of the display.
- 25 9. A terminal, or method substantially as hereinbefore described with reference to the accompanying figures 3, 4a and 4b and/or as shown in the accompanying figures 3, 4a and 4b.
- 10.A terminal for displaying information on a display, said information comprising elements, wherein an element is either provided with a
- 30

continuous length presenting a length which is equal to or greater than the size of said display, or a wrapped length presenting a length which is less than the size of said display, said terminal comprising

- a display for displaying said information,
- 5 - means for setting a first type of elements to be displayed as a continuous length item and a second type of element to be displayed as a wrapped length item,
- means for identifying said first type of element when acting in a text to be displayed, and
- 10 - means for displaying the first and second type of elements according to their setting.

ABSTRACT

A method and terminal for displaying information on a display, where the information is provided with elements. An element is either having a continuous length presenting a length which is equal to or greater than the size of said display, or a wrapped length presenting a length which is less than the size of said display. The display is further provided with a user interface having a menu structure of items. The user interface is provided with a selectable continuous length item and/or a wrapped length item. The information is displayed according to the selection made in the menu structure of the user interface, in order to allow the user to toggle between continuous length and wrapped length.

15 (Fig. 3)

FIG. 1






FIG. 2

THIS PAGE BLANK (USPTO)

Fig.3


2/4



THIS PAGE BLANK (USPTO)

Fig. 4a


3/4



THIS PAGE BLANK (USPTO)

Fig. 4b

4/4



*** THE END ***

THIS PAGE BLANK (USPTO)